

# TSS PRINTER DRIVER

The Printer Driver is an internal program designed to allow the use of the line printer for listing large files. It will eventually be converted to run under the disk system.

The Printer Driver runs under the Bead and is called with the standard calling sequences.

ie C, PRINTER, S, fname, user name  
and

RECALL, PRINTER, CLASS, fname, user name

where fname, username are the file name and user name of the file to be printed.

Immediately after being called the Printer driver will ask whether the first character of each line should be interpreted as a scope carriage control character or not. If this action is desired type YES @. The printer driver looks for a Y in col. 1. Therefore Y @ is equivalent to YES @ while YES @ is not. The default option (ie, no Y in col. 1) will be single spacing with auto page eject and all characters printed. The first character of each line being printed

# PRINTER DRIVER

# ASCII - DEC DISPLAY CODE MAPPING

## ASCII

PRINTER  
CHAR

## ASCII

DEFLGII - JAK-209 QRSUJ-C>3X>ML / M-1, Q9VJ49

PRINTER CHAI

וְעַל־יְהוָה תִּתְּחַנֵּן וְאֶל־מִצְרָיִם תִּתְּחַנֵּן

\*  
ASC II

PRINTER  
CHAR

h i j k l m n o p q r s t u v w x y z ~ )  
~

all others - [ ]